

## DIRECTIONS FOR USE

Apply only as directed.

Use Andersons Nutri DG<sup>®</sup> Dispersing Granule Technology 0-0-25 for greens and tees where a potassium application is desired or when manganese and magnesium are needed to help correct or prevent deficiencies during the growing season.

Watering in this product will disperse each granule into thousands of particles. This will facilitate the movement of the nutrients into the soil. This particle dispersion will greatly reduce ball, shoe and mower pickup - minimizing nutrient loss.

Application to wet, close-cut golf turf may result in foliar staining, which will discolor the turf to a brown/black appearance. This will occur even if immediate irrigation or rainfall occurs. Be sure to apply this product to dry turf only.

### Application Rates:

0.98 - 2.44 kg/100 m<sup>2</sup> (2.00 - 5.00 lbs/1,000 sq. ft.)

Apply at the rate for the amount of Potash desired.

Use Rate kg/100 m <sup>2</sup>	K <sub>2</sub> O kg/100 m <sup>2</sup>	Use Rate lbs/1,000 sq. ft.	K <sub>2</sub> O lbs/1,000 sq. ft.	20 kg bag treats	20 kg bag treats
0.98	0.24	2.00	0.50	2,050 m <sup>2</sup>	22,000 sq. ft.
1.46	0.37	3.00	0.75	1,370 m <sup>2</sup>	14,700 sq. ft.
1.95	0.49	4.00	1.00	1,020 m <sup>2</sup>	11,000 sq. ft.
2.44	0.61	5.00	1.25	820 m <sup>2</sup>	8,800 sq. ft.

### For all applications:

- Immediately after application, apply a minimum of 5.1 mm (0.2 inches) of water to avoid staining and foot printing.
- Apply only at low rates if temperatures are 29° C (85° F) or above.
- Cold weather (lower than 7° C/45° F) can result in slower particle dispersion.

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

## GUARANTEED ANALYSIS

Soluble Potash (K <sub>2</sub> O) .....	25.00%
Magnesium (Mg) .....	4.00%
4.00% Water Soluble Magnesium (Mg)	
Sulfur (S) .....	13.70%
13.70% Combined Sulfur (S)	
Manganese (Mn) .....	3.00%
3.00% Water Soluble Manganese (Mn)	

Constituent Materials: sulfate of potash magnesia, potassium sulfate and manganese sulfate.

U.S. Patent #6,884,756

### Storage and Use:

Store in a clean, dry place.

Reseal opened bag by folding top down and securing.

Use only clean, dry spreaders.

Do not leave unused product in spreaders.

### IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

### WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

### LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/PROVINCE/JURISDICTION TO STATE/PROVINCE/JURISDICTION.

Product of USA

The Andersons logo is a registered trademark of The Andersons, Inc.; Nutri DG is a trademark of The Andersons, Inc.; Proactin is a registered trademark of Vitech Enterprises, Inc.

## Suggested Spreader Settings

The suggested spreader settings are not intended to replace calibration.  
Please calibrate your spreader before applying product.

SPREADER	GROUND SPEED	WIDTH OF COVERAGE	0.98 kg/100 m <sup>2</sup> (2.00 lbs/1,000 sq. ft.)	1.46 kg/100 m <sup>2</sup> (3.00 lbs/1,000 sq. ft.)	1.95 kg/100 m <sup>2</sup> (4.00 lbs/1,000 sq. ft.)	2.44 kg/100 m <sup>2</sup> (5.00 lbs/1,000 sq. ft.)
ANDEpro 2000, AccuPro 2000, SR-2000 (cone 9 for AccuPro & SR-2000)	4.8 km/hr (3 mph)	3.0 m (10 feet)	H 1/2	I	I 3/4	K
SS-2 Drop	4.8 km/hr (3 mph)	overlap wheels	3	3 3/4	4 1/4	4 3/4
R-8, R-8A (cone 9)	4.8 km/hr (3 mph)	3.0 m (10 feet)	G 1/2	H	H 3/4	I 1/2
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) (Pattern II-B)	7.2 km/hr (4.5 mph)	7.9 m (26 feet)	Not Recommended	3 3/4	4 1/4	4 1/2
Vicon (03 Series)	7.2 km/hr (4.5 mph)	6.7 m (22 feet)	12	13	16	18



Manufactured by:  
The Andersons Lawn Fertilizer Division, Inc.  
P. O. Box 119  
Maumee, OH 43537  
USA



**Net Weight 20 kg (44.1 lbs.)**  
**APPCK25MDG4**

C8 (APPBLKPNDBG)